



5000 Series Auto Slacks

P/N: L1048SB

OTR introduces the 5000 Series Automatic Brake Adjuster for the top 4 applications. The OTR 5000 Series provides the durability and precision adjustment needed for optimum brake performance. Here's how:



- ▶ Monitors the applied stroke, with the initial reading of shoe to drum clearance when the brake drums are closest to ambient temperature to avoid over adjustment. Adjusts when the pre-set shoe to drum clearance is exceeded.
- ▶ Monitoring the applied stroke vs. the release stroke also avoids over adjustment from deflection of other brake system components. This deflection is greatest when the drum temperature is highest which is closer to brake release vs. brake application.
- ▶ Factory lubricated and sealed to protect against contamination. Periodic lubrication is recommended every 6 months or 50,000 miles.
- ▶ Drilled and grooved spline wheel facilitates lubrication to camshaft splines reducing rust.
- ▶ Non-handed design requires no external brackets for easy installation and replacement.

P/N	Cam Diameter	Splines	Arm Length	Gunite® Cross
OTR51132	1.5"	10	5.5"	AS1132
OTR51133	1.5"	10	6"	AS1133
OTR51140	1.5"	28	5.5"	AS1140
OTR51141	1.5"	28	6"	AS1141

OTR 5000 Series Auto Slacks are the SMART choice to meet the high demands of today's braking systems because there's NO TIME FOR DOWNTIME